



(19) **United States**

(12) **Patent Application Publication**
Yuh

(10) **Pub. No.: US 2021/0331944 A1**

(43) **Pub. Date: Oct. 28, 2021**

(54) **SYSTEM AND METHOD FOR SORBITION
DISTILLATION**

(71) Applicant: **Howard Y. Yuh**, Yardley, PA (US)

(72) Inventor: **Howard Y. Yuh**, Yardley, PA (US)

(21) Appl. No.: **17/367,769**

(22) Filed: **Jul. 6, 2021**

Related U.S. Application Data

(60) Continuation of application No. 16/590,758, filed on Oct. 2, 2019, now Pat. No. 11,084,735, which is a continuation of application No. 16/164,942, filed on Oct. 19, 2018, now Pat. No. 10,464,825, which is a division of application No. 15/637,236, filed on Jun. 29, 2017, now Pat. No. 10,150,681.

(60) Provisional application No. 62/356,126, filed on Jun. 29, 2016.

Publication Classification

(51) **Int. Cl.**

- C02F 1/04* (2006.01)
- B01J 20/20* (2006.01)
- B01J 20/04* (2006.01)
- B01J 20/283* (2006.01)
- B01J 20/28* (2006.01)
- F28D 15/02* (2006.01)
- B01D 1/00* (2006.01)
- B01D 3/04* (2006.01)
- B01D 15/08* (2006.01)
- C02F 1/12* (2006.01)
- C02F 1/14* (2006.01)
- C02F 1/26* (2006.01)

- H01L 31/054* (2006.01)
- H02S 20/10* (2006.01)
- H02S 20/32* (2006.01)
- H02S 40/44* (2006.01)
- F24S 23/79* (2006.01)
- F24S 20/20* (2006.01)
- F24S 23/77* (2006.01)

(52) **U.S. Cl.**

CPC *C02F 1/048* (2013.01); *B01D 1/26* (2013.01); *B01J 20/046* (2013.01); *B01J 20/283* (2013.01); *B01J 20/28014* (2013.01); *B01J 20/28004* (2013.01); *F28D 15/0275* (2013.01); *B01D 1/0035* (2013.01); *B01D 3/04* (2013.01); *B01D 15/08* (2013.01); *C02F 1/12* (2013.01); *C02F 1/14* (2013.01); *C02F 1/265* (2013.01); *H01L 31/0547* (2014.12); *H02S 20/10* (2014.12); *H02S 20/32* (2014.12); *H02S 40/44* (2014.12); *F24S 23/79* (2018.05); *F24S 20/20* (2018.05); *F24S 23/77* (2018.05); *B01D 2253/106* (2013.01); *B01D 2253/102* (2013.01); *Y02B 10/70* (2013.01); *Y02E 10/52* (2013.01); *Y02W 10/37* (2015.05); *Y02B 10/20* (2013.01); *B01J 20/20* (2013.01)

(57)

ABSTRACT

A system for distilling water is disclosed. The system comprises a heat source, and a plurality of open-cycle adsorption stages, each stage comprising a plurality of beds and an evaporator and a condenser between a first bed and a second bed, wherein each bed comprises at least two vapor valves, a plurality of hollow tubes, a plurality of channels adapted for transferring water vapor to and from at least one of the condenser or the evaporator, a thermally conductive water vapor adsorbent, and wherein each vapor valve connects a bed to either the condenser or the evaporator.

